

ARCHITECTURAL ZINC



Superior performance for superior design

Jarden Zinc's Standing Seam Panel System

The versatility and durability of zinc makes it an excellent choice as a material for roofing and facade applications. You can use the Jarden Zinc Single Lock or Double Lock Standing Seam to create traditional clean lines up to 35' in length.

Zinc is highly malleable and can be formed into just about any shape, allowing for incredible freedom in design. In addition to its natural self-healing properties, zinc can provide decades of maintenance free protection.

Available in Architectural Series and Presidential Series finishes.



jardenzinc.com

ARCHITECTURAL ZINC

Contact our sales team for more information about our company and products.

Toll-Free:
(800) 251-7506

Phone:
(423) 639-8111

Fax:
(423) 639-3125

Email:
sales@jardenzinc.com

Website:
jardenzinc.com

Address:
Jarden Zinc
P.O. Box 1890
Greeneville, TN 37744-1890



Superior performance for superior design

Single-Lock, Standing Seam Panel System

This traditional single-lock system provides a solid seam profile for facades and applications using your traditional seaming machine or hand-produced techniques.

Jarden's low height 1" (25mm) standing seam appeals to designers looking to present a softer visual with increased straightness. This is especially true for more complex shapes, or a distinctive "high-tech" appearance. Our 1.5" (38mm) standing seam offers greater line contrast and shadowing for a more traditional, even historic look.

Double-Lock, Standing Seam Panel System

The distinctive vertical lines of the double lock standing seam are perfectly paired with the timeless patina of Jarden zinc. Due to its durability and malleability, zinc is a perfect material for flat, curved or tapered panels.



Specifications

Panel Depth: 1" or 2" (25.4 or 51mm)

Coverage:*

1" depth - 12"-21.75" (304.80–552.45 mm)

2" depth - 12"-18.5" (304.80–469.9 mm)

Maximum Length: 35' 0" (10.668mm)

Material Thickness: 0.0276" (0.70mm) or 0.031" (0.80mm)

Alloy: Jarden Alloy 710 (EN988/ASTM1179)

Available Finishes: Architectural and Presidential Series

*Jarden Zinc recommends using BreeZemat™ 10 or 20 beneath roofing or facade panel to ensure proper ventilation.

A full range of accessories, stainless steel expansion and fixing clips, ventilation/drainage mat, trims and flashings, pre-notched panels, engineered shop drawings, plumbing flashings in zinc are available.